NORDICLIGHTS

SCORPIUS PRO 2500

The classic work light, redesigned from scratch to be an even better fit for construction. The Scorpius PRO 2500 is built to handle any task you throw at it. Suitable for 12-24V systems, this work light features high vibration resistance, a scratch-resistant coating, and excellent lumen per watt-ratio. The Scorpius PRO 2500 has an operational lumens output of 2300 lm.

Not all products are available in all markets. During continuous improvement specifications and design are changing. All values are nominal values. Illustrations do not necessarily show the design of every version and some features are version specific. The lumens output varies depending on lens colour.

TECHNICAL DATA

Theoretical Lumens Output	3700 lm
Operational Lumens Output	2300 lm
Color Temperature	5700 K
Nominal Voltage DC	12 - 24 V
Input Voltage DC	9 - 32 V
Power Consumption	19 W
Nominal Current at	24V=0.8A, 12V=1.6A
Connector	Built-in Deutsch DT-2 (2-pin)
Mount	Single Bolt M10
Shock	60G

Vibration	15.44Grms 10-2000Hz
Lens	Plastic
Body / Housing	Aluminum
Weight	1.1 kg
IP Rating	IP68, IP6K9K
Salt Spray Test	ISO 9227 240H
EMC	CISPR 25 Class 5, EN12895, ISO 13766, ISO 14982, ISO 7637-2
Operating Temperatures	-40°C... +85°C (Overheat protected)
Part Numbers	Flood: 984-9015, Wide Flood: 984-9014, High Beam: 984-9016

NORDIC LIGHTS®
NORDIC LIGHTS Ltd.
P.O. Box 36, Bennäsvägen 155
FI-68601 Jakobstad, FINLAND
Tel. +358 20 1345 100
www.nordiclights.com

CONNECTORS

Built-in Deutsch DT-2 (2-pin)

KEY FEATURES

- Vibration and shock resistant
- Scratch-resistant coating
- For harsh conditions

LIGHT PATTERNS

Scorpius PRO 2500, 2300lm
Wide Flood



Scorpius PRO 2500, 2300lm
Flood



Scorpius PRO 2500, 2300lm
High Beam



DRAWINGS

NORDIC LIGHTS®
NORDIC LIGHTS Ltd.
P.O. Box 36, Bennäsvägen 155
FI-68601 Jakobstad, FINLAND
Tel. +358 20 1345 100
www.nordiclights.com


108mm (4.3")
108mm (4.3")
NORDICLIGHTS
84mm (3.3")
42mm
(1.6")
110mm (4.3")
137mm (5.4")